



www.riso.co.za

RETHINK MONOPRINT



RISO SF5030 E

RISO SF5030 E

| | | |
|---|---|--|
| Master Making/Printing Methods | | High-speed digital master-making/Fully automatic printing |
| Original Type | | Book or sheet |
| Master Making Time*1 | Quick Master Making mode | Approx. 20 seconds (A4, short-edge feed) |
| | Normal Master Making mode | Approx. 22 seconds (A4, short-edge feed) |
| Resolution | Scanning | 600 dpi × 600 dpi |
| | Printing | 300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi |
| Maximum Scanning Area | | 297 mm × 432 mm |
| Print Paper Weight | | 46 gsm to 157 gsm |
| Print Paper Size | | 100 mm × 148 mm to 310 mm × 432 mm |
| Maximum Printing Area | | 210 mm × 290 mm |
| Paper Feed Tray Stacking Capacity | | 1000 sheets*2, stacking height of 110 mm or lower |
| Paper Receiving Tray Stacking Capacity | | 1000 sheets*2, stacking height of 110 mm or lower |
| Print Speed | | 5 levels: 60, 80, 100, 120 and 130 ppm |
| Print Position Adjustment | | Horizontal: ±15 mm, Vertical: ±10 mm |
| Image Processing Mode | | Line, Photo, Duo, Pencil |
| Print Reproduction Ratio | | Zoom: (50% to 200%), 100% reduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%) |
| User Interface | | LCD panel |
| Functions | | Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto*3, Speed, Density, Print Position, Program A/B, D-feed check, Slip sheet sorting, Job Separation*4, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Paper Memory Print, Auto Sleep Setting, Auto Power-OFF Setting, ECO mode, RISO iQuality System |
| PC Interface | | USB2.0, Ethernet:100BASE-TX, 10BASE-T*5 |
| Ink Supply | | Full automatic (1000 ml/cartridge) |
| Master Supply/Disposal | | Full automatic (A4: approx. 295 sheets per roll)/Disposal capacity: approx. 100 sheets |
| Power Source | | AC 100-120 V 3.4 A, AC 220-240 V 1.6 A, 50-60 Hz |
| Power Consumption | Standard | Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower |
| | Optional Accessories Connected*6 | Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower |
| Dimensions (W×D×H) | In use | 1415 mm × 670 mm*7 × 1065 mm*8 |
| | In storage | 780 mm × 670 mm*7 × 1065 mm*8 |
| Required Space (W×D×H) | | 1415 mm × 1240 mm × 1515 mm*8 |
| Weight | | 100 kg*9 |

*1 Measurement value when set to 100% reproduction ratio.

*2 When using the following weight of paper: 64 gsm to 80 gsm

*3 Usable when the optional auto document feeder is installed.

*4 Usable when the optional Job Separator is installed.

*5 RISO Network Kit S10 (optional) is required for connecting to the network.

*6 When all the following optional accessories are installed, Auto Document Feeder, Job Separator, IC Card Reader.

*7 The depth does not include the stabilizers for the dedicated stand.

*8 The height includes the dedicated stand.

*9 The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

Optional Accessories



RISO FII Type Drum
Enables color printing.
(Case included)



RISO Auto Document Feeder VII
Scans multiple documents automatically.



RISO Job Separator IV, NIII
Enables easy separation of printed sheets by inserting tape strips.



Card Feed Kit
Compatible with paper weight 100 gsm to 400 gsm.
*Please contact a RISO sales representative for the kinds of paper that may be used.



RISO Stand D Type III
Deluxe and with doors for convenient storage with a neat appearance.



RISO Stand N Type III
Sturdy open-front stand also offers convenient storage of consumables.

- IC Card Reader Activation Kit RG
- RISO Network Kit S10
- RISO Printer driver for Macintosh
- Envelope Feed Kit
Compatible with paper weight 50 gsm to 120 gsm.

riso iQualitySystem™

The RISO i Quality mark indicates a RISO product compatible with the RISO i Quality System.

RISO INK FII Type Color (1000 ml)

RISO MASTER FII Type (A4: 295 sheets)

RISO INK FII Type Black (1000 ml)

and RISO, RISO i Quality System and RISO i Quality mark are trademarks or registered trademarks of RISO KAGAKU CORPORATION in the United States and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.
Copyright ©2019 RISO KAGAKU CORPORATION. All rights reserved.

For more details please contact:



RISO KAGAKU CORPORATION
5-34-7 Shiba, Minato-ku, Tokyo 108-8385 Japan
<https://www.riso.com/>